



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

### **Section 1: Identification**

**Chemical Product Name/Identifier:** Skybond® 701 Polyimide Resin

**CAS Number:** Mixture

**Trade Names and Synonyms:** Solution of aromatic polyimide precursor in ethanol and methanol.

**Recommended Use and Restrictions on Use:** Polyimide Resin

**Company Information:** Industrial Summit Technology Corporation  
250 Cheesecake Road  
Parlin, NJ 08859

**Telephone:** Product and Sales Information: 732-238-2211

**Emergency Phone:** CHEMTREC: 1-800-424-9300

### **Section 2: Hazards Identification**

**OSHA HCS Status:** This product is a hazardous chemical, as defined by OSHA at 29 CFR 1910.1200. Hazards identified are based on hazards of the ingredients.

**Relevant Route of Exposure/Target Organs:** Dermal, Eyes, Inhalation, Respiratory System

#### **OSHA/GHS Signal Word and Hazard Statements:**

**DANGER:** Highly flammable liquid and vapor. Causes skin irritation. Causes eye irritation. Toxic in contact with skin. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility of the unborn child. Causes damage to organs (respiratory system). May damage organs (liver, kidney, blood) through prolonged or repeated exposure. Harmful if inhaled. Toxic if swallowed. May cause cancer. Harmful to aquatic life with long lasting effects.

#### **OSHA/GHS Classification and Pictograms:**

Flammable liquid (Category 2) H225  
Acute toxicity, inhalation (Category 3) H331  
Acute toxicity, oral (Category 3) H302  
Acute toxicity, dermal (Category 3), H311  
Skin irritation (Category 2) H315  
Eye irritation (Category 2A) H319  
Skin sensitization (Category 1) G370  
Germ cell mutagenicity (Category 2) H341  
Carcinogenicity (Category 2) H351  
Reproductive toxicity (Category 1B) H360  
Specific target organ toxicity - single exposure (Category 3, respiratory system) H335  
Specific target organ toxicity - repeated exposure (Category 2, liver) H373  
Acute aquatic toxicity (Category 2) H401  
Chronic aquatic toxicity (Category 2) H411

For the full text of the H-Statements mentioned in this Section, see Section 16.



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin



### OSHA/GHS Precautionary Statements:

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection specified in Section 8.

Wash hands and exposed skin thoroughly after handling. Wear protective gloves, eye and face protection.

Avoid breathing mist, vapors, and spray. Use only outdoors or in well-ventilated area. Obtain special instructions before use.

Contaminated work clothing must not be allowed out of the workplace.

#### Response

In case of fire: Use water spray, foam, dry chemical, carbon dioxide, or any Class B extinguishing agent.

If exposed or concerned: get medical advice/attention.

If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash skin with plenty of water/shower. Specific treatment: see Section 4 for First Aid instructions. If skin irritation or rash occurs: Get medical advice/attention. Call a poison center/doctor if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

#### Storage

Store in a well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

**GHS Hazard and Precautionary Statement Codes:** See Section 16.

### Section 3: Composition/Information on Ingredients

**Chemical Product Name:** Skybond 701 Polyimide Resin

Component	CAS #	Weight %
1,2-Benzenedicarboxylic acid, 4,4'-carbonylbis-ar, ar'-diethyl ester, compd with with 1,3-benzenediamine	65701-07-7	60.41
Methyl isobutyl ketone	108-10-1	≈0.7
Ethanol	64-17-5	≈36
1,3 -Diaminobenzene (m-phenylenediamine)	108-45-2	≈12.5
Methanol	67-56-1	<0.2

### Section 4: First-Aid Measures

**Skin Contact:** Immediately wash skin with soap and water. Remove contaminated clothing. Get medical attention. Wash contaminated clothing before reuse.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**Inhalation:** Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get medical attention. Remove material from eyes, skin, and clothing.

**Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

**Most Important Symptoms/Effects:** Skin and eye irritation. May cause respiratory irritation or distress. May cause cancer and damage fertility or the unborn child. Repeated or prolonged contact may cause allergic skin reaction in some people. May cause liver damage.

**Indication of Immediate Medical Attention and Special Treatment Needed:** Get medical attention immediately if product comes into contact with skin or eyes, or if it is inhaled or ingested.

### Section 5: Fire-Fighting Measures

**Extinguishing Media:** water spray, foam, dry chemical, carbon dioxide, or any Class B extinguishing agent.

**Hazardous Combustion Products:** Oxides of carbon produced when burned.



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

**Protective Equipment:** Firefighters and others who may be exposed to products of combustion (see Hazardous Decomposition Products in Section 10) should be equipped with self-contained breathing apparatus and full protective gear. Equipment should be thoroughly decontaminated after use.

**Fire Fighting Procedures/Precautions:** Keep away from heat/sparks/open flames/hot surfaces. Keep personnel removed and upwind of fire. Closed containers exposed to heat may build up pressure. Use water spray to keep exposed containers and equipment cool. Use water spray to cool containers and tanks.

### Section 6: Accidental Release Measures

**Personal Precautions:** Review Firefighting Measures and Handling sections before proceeding with clean up. Take precautions to avoid eye, skin, and respiratory exposure. Should exposure occur, see Section 4 for first aid measures. Flammable vapors can accumulate in low areas and form explosive concentrations.

**Protective Equipment:** Use appropriate personal protective equipment during clean up. See Section 8.

**Emergency Procedures:** Maintain adequate ventilation. Shut off all sources of ignition. No heat, sparks, or flame in the area.

**Methods/Materials for Containment and Cleaning Up:** Dike spill. Remove sources of sparks, flame, or hot surfaces. Absorb spill with commercial absorbent material and place in suitable containers for disposal. Dispose of as hazardous waste (see section 13). Do not discharge into waterways or sewer systems without proper authority. Dispose of in accordance with government regulations.

### Section 7: Handling and Storage

**Precautions:** Avoid breathing vapors or mist. Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. Keep away from heat, sparks and flames.

**Storage:** Keep container in a cool place. Store below 50 C (122 F). Keep container tightly closed. Store in accordance with National Fire Protection Association recommendations.

### Section 8: Exposure Controls/Personal Protection

#### Exposure Limits:

Component	OSHA PEL	ACGIH TLV	OARS/WEEL**	I.S.T/AEL*
Methyl isobutyl ketone	50 ppm 205 mg/m <sup>3</sup> 75 ppm STEL	20 ppm	NA	NA
1,2-Benzenedicarboxylic acid, 4,4'-carbonylbis-ar, ar'-diethyl ester, compd with	NA	NA	NA	NA



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

with 1,3-benzenediamine				
Ethanol	1000 ppm 1900 mg/m <sup>3</sup>	1000 ppm	NA	NA
1,3 -Diaminobenzene (m-phenylenediamine)	NA	0.1 mg/m <sup>3</sup>	NA	NA
Methanol	200 ppm 260 mg/m <sup>3</sup>	200 ppm 250 STEL	NA	NA

\* AEL is I.S.T's acceptable limit. Where governmentally imposed occupational exposure limits, which are lower than the AEL are in effect, such shall take precedence.

\*\* Occupational Alliance for Risk Science, workplace environmental exposure level.

**Engineering Controls:** Use ventilation that is adequate to keep employee exposure to airborne concentrations below recommended exposure limits. Provide natural or mechanical ventilation to control exposure levels below airborne exposure Limits (see section 6 above). If practical use, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment. Consult NFPA Standard 91 for design of exhaust system.

### Personal Protection Measures/Equipment:

**Skin Protection:** Wear appropriate chemical resistant gloves and clothing to prevent skin contact. Consult glove manufacturer to determine appropriate type of glove for given application. Wear chemical safety goggles, a face shield and a chemical resistant apron when splashing is likely. Wash immediately if skin is contaminated. Remove contaminated clothing promptly and launder before reuse. Clean protective equipment before reuse. Provide a safety shower at any location where skin contact can occur. Wash hands and exposed skin thoroughly after handling. Repeated or prolonged contact may cause allergic skin reaction in some people.

**Eye Protection –** Wear eye and face protection. Wear chemical goggles that meet ANSI Z87 standards and/or are tested and approved under appropriate government standards. Eyewash stations should be easily accessible.

**Respiratory Protection –** Avoid breathing vapor and/or mist. Use NIOSH/MSHA approved respiratory protection equipment (full face piece recommended) when airborne exposure limits (see below) are exceeded. If used, full face piece replaces need for face shield and chemical goggles. Consult respirator manufacturer to determine the appropriate type of equipment for given application. Observe respirator use limitations specified by NIOSH/MSHA or the manufacturer. Respiratory protection programs must comply with 29 CFR 1910.134.

### Section 9: Physical and Chemical Properties

**Appearance (physical state, color, etc.):** Brown viscous liquid

**Odor:** Amine-like

**Odor Threshold:** Not known



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

**pH:** Not known

**Melting Point/Freezing Point:** Not known

**Initial Boiling Point:** Not known

**Flash Point:** 20°F

**Evaporation Rate:** Not known

**Flammability:** Flammable liquid

**Upper/Lower Flammability or Explosive Limits:** Not known

**Vapor Pressure:** 60 mm Hg

**Vapor Density:** 1.6

**Relative Density/Specific Gravity:** 1.05 – 1.10

**Solubility:** Slight in water

**Partition Coefficient:** Not known

**Auto-ignition Temperature:** Not known

**Decomposition Temperature:** Not known

**Viscosity:** 100-700 cps at 25°C

**% Volatiles:** Not known

**Solids after Cure:** 46%

NOTE: This physical data are typical values based on material tested by may vary from sample to sample. Typical values should not be considered as a guaranteed analysis of any specific lot or as a specification for the product.

### **Section 10: Stability and Reactivity**

**Reactivity:** Not known

**Chemical Stability:** Not known.

**Hazardous Reactions:** Not known

**Conditions to Avoid:** All sources of ignition – heat, sparks, and open flames. Volatiles given off during cure - Ethanol.

**Incompatible Materials:** Strong oxidizing agents, strong alkali

**Hazardous Decomposition Products:** Carbon monoxide, nitrogenous products

**Hazardous Polymerization:** Does not occur

### **Section 11: Toxicological Information**

**Relevant Route of Exposure/Target Organs:** Dermal, Eyes, Inhalation, Respiratory System



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

**Symptoms:** Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause respiratory tract irritation. May damage fertility or the unborn child.

### **Delayed and Immediate Effects:**

Eye effects:

Eye contact with the liquid or vapor may initially result in irritation with discomfort, tearing, or blurring of vision. Low vapor concentrations caused eye irritation in some individuals.

Skin effects: Skin contact may initially result in irritation with discomfort or rash.

Respiratory effects: Inhalation may result in irritation of the upper respiratory passages, with dizziness, nausea, loss of appetite and headache.

### **Health Effects Summary**

#### **Chronic Effects (Following Short and Long Term Exposure):**

The following information summarizes experience and results of scientific investigations reviewed by health professionals for hazard evaluation of Skybond® 701 polyimide resin and development of Precautionary Measures and Occupational Control Procedures recommended in this document. Industrial Summit Technology Corp has not conducted studies on SKYBOND® 701 polyimide resin and no data was obtained in a search of the available scientific literature. However, toxicity information is available on representative polyimide resins.

Inhalation and skin contact are expected to be the primary routes of occupational exposure of SKYBOND® 701 Polyimide Resin.

Occupational exposure to this material has not been reported to cause significant adverse human health effects. However, SKYBOND 701 polyimide resin is considered to cause severe eye irritation based on animal studies. The organic solvents described below, have been reported to cause eye, skin and respiratory tract irritation and may contribute to the health effects of this material. These solvents also possess narcotic-like properties; excessive exposure may result in headache, dizziness, in coordination, nausea, loss of appetite and loss of consciousness.

#### Toxicological Data

Industrial Summit Technology Corporation has not conducted studies on SKYBOND 701 polyimide resin and no data was obtained in a search of the available scientific literature. However, toxicity information is available on representative polyimide resins.

Single exposure (acute) animal studies conducted on representative polyimide resins indicate that these materials are slightly toxic or practically nontoxic orally (rats) and practically nontoxic after skin application (rabbits). They range from practically nonirritating to moderately irritating to rabbit skin and moderately irritating to corrosive to rabbit eyes.

SKYBOND 701 has not been tested for the potential to produce allergic skin reaction. However, no allergic skin reaction was observed in guinea pigs following repeated skin exposure to related SKYBOND polyimide resins.



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

Data from Industrial Summit Technology Corporation, studies, and from the available scientific literature on the components of SKYBOND® 700 polyimide resin which have been identified under the criteria of the OSHA Hazard Communication standard (29 CFR 1910.1200) are discussed below.

### Meta-phenylenediamine (m-PDA)

Meta-phenylenediamine (m-PDA) is used in the production of this polyimide resin. Single-dose (acute) animal studies indicate that m-PDA is moderately toxic orally (rats) and inhalation (rats) and slightly toxic after skin application (rabbits). It is moderately irritating to rabbit eyes and skin. Allergic skin reactions have been reported in various laboratory animals repeated skin application tests. Rats given this material orally for 90 days showed increased liver and kidney weights and liver damage.

No significant increase in tumors were reported in a drinking water study (mice, 78 weeks), skin painting study (mice 24 months), or long term feeding study (rats, mice). No birth defects were reported in rats given this material orally during pregnancy, even at levels which produced toxic effects to the mother.

Adverse genetic effects have been reported in standard tests using bacterial and animal cells. Both positive and negative genetic changes were reported in standard tests using animals. No adverse genetic changes were reported in standard tests with human cell cultures and insects.

### Ethanol

Swallowing of ethanol also causes central nervous system effects and digestive tract effects; large amounts may cause respiratory failure leading to death. Other effects of ethanol related to repeated intake of alcoholic beverages including nutritional deficiencies, liver, and pancreas damage and secondary blood cell changes. Repeated consumption of ethanol (alcoholic beverages) by pregnant women is reported to produce adverse effects on the development of their offspring ("fetal alcohol syndrome").

Single-dose (acute) animal studies indicate that ethanol is practically non-toxic orally (rats), after skin application (rabbits) and after inhalation (rats). It is mildly to severely irritating to rabbit eyes and practically nonirritating to moderately irritating to rabbit skin. It is practically non-toxic by inhalation (Rat LD50-20,000 ppm, 10-hr. exposure). Various morphological functions and biochemical changes including changes in the heart muscle, liver, CNS, and blood cells have been reported for experimental animals given ethanol orally. Repeated inhalation exposures produced liver damage in rabbits, while other treatment-related effects were reported in pigs, dogs, and monkeys. Rats exposed by skin application to a 50o/o solution of ethanol showed only temporary skin irritation. Several species of laboratory animals have been exposed to ethanol by various routes to determine effects on an offspring. While susceptibility varies with each species, birth defects have been consistently reported in many of the species tested (mouse, rat, pig, guinea pig, monkey). Ethanol produced genetic changes in standard tests using human volunteers and animals and yeast cells. No genetic changes were reported in standard tests using bacterial or animal cells, negative responses were reported in assays using human cells.

Ethanol in alcoholic beverages is listed as a substance which is "carcinogenic to humans" by the International Agency for Research on Cancer (IARC Monographs Vol. 44). This IARC listing is based on evidence of carcinogenicity of alcoholic beverages following long-term consumption of alcoholic





# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

beverages. Epidemiological studies report increased incidence of mouth and throat cancer in humans after long-term consumption of alcoholic beverages. Higher risk is associated with the drinking of dark liquors and for smokers who consume alcoholic beverages.

### Methanol

In addition to the effects noted, significant swallowing of methanol also causes central nervous system effects and possible damage to the kidneys. Temporary or permanent visual disturbances are commonly seen with methanol poisoning in man, although permanent loss of vision is generally associated with poisoning following swallowing. Initial visual symptoms include blurring or dimness, changes in color perception, pain and tenderness, and dilated unreactive pupils.

### Carcinogenicity:

Methyl isobutyl ketone; IARC Group 2B: Possibly carcinogenic to humans

Other components of this product are not classified by NTP, IARC, or OSHA as carcinogens.

### **Section 12: Ecological Information**

96-hr LC50 Bluegill Sunfish: 380 mg/l, Practically Non-Toxic

96-brLC 50 Rainbow Trout: 340 mg/l Practically Non-Toxic

48-h LC50 Daphnia Magna: 16 mg/l, Slightly Toxic

**Persistence and Degradability:** Not known

**Bioaccumulative Potential:** Not known

**Mobility in Soil:** Not known

### **Section 13: Disposal Information**

Do not discharge into waterways or sewer systems. Dispose of in accordance with government regulations. US EPA waste code D001 (ignitability characteristic).

### **Section 14: Transport Information**

UN Number: 1866

Proper shipping name: Resin solution

Hazard class 3

Packing group: III

### **Section 15: Regulatory Information**

**TSCA Inventory Status:** All ingredients are on the TSCA inventory.

**SARA Title III Section 311/312 Hazard Categories:** Immediate (acute), Delayed (chronic), Fire



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

**SARA Title III Section:** The component listed below is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 (EPCRA or SARA Title III) and 40 CFR 372.

Component	CAS #	313 Listed	%	RQ (lb)
Methyl isobutyl ketone	108-10-1	Yes	≈0.1	5000
1,2-Benzenedicarboxylic acid, 4,4'-carbonylbis-ar, ar'-diethyl ester, compd with with 1,3-benzenediamine	65701-07-7	No	60.41	--
Ethanol	64-17-5	No	36.2	--
Methanol	67-56-1	Yes	<0.2	5000

**CERCLA RQ:** See table above.

**California Proposition 65:** This product contains Methyl isobutyl ketone, which is known to the State of California to cause cancer.

### **Section 16: Other Information**

**Date of Preparation or Revision:** June 01, 2015

#### **GHS Label Hazard Statement Codes**

Signal Word: DANGER

H225: Highly flammable liquid and vapor.

H311: Toxic in contact with skin

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H331: Toxic if inhaled

H360: May damage fertility or the unborn child

H370: Causes damage to organs

H401: Toxic to aquatic life

H411: Toxic to aquatic life with long lasting effects

#### **GHS Label Precautionary Statement Codes**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from flames and hot surfaces. – No smoking.

P260: Do not breathe dust/ fume/ gas/ mist/ vapors/ spray



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace

P280: Wear protective gloves, eye and face protection.

P281: Use personal protective equipment as required.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P251+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P307+P313: If exposed: Call a POISON CENTER or doctor/ physician.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P321: In case of skin contact, immediately wash skin with soap and water. Remove and wash contaminated clothing before reuse.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P362+P364: Take off contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use water fog, dry chemical, foam, or CO<sub>2</sub> for extinction.

P403+P233+P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

### Abbreviations

ALC	Approximate Lethal Concentration
ANSI	American National Standards Institute
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	US Code of Federal Regulations
CO <sub>2</sub>	Carbon dioxide
DOT	US Department of Transportation
EPCRA	Emergency Planning and Community Right to Know Act
GHS	UN Globally Harmonized System of Classification and Labeling of Chemicals
HCS	Hazard Communication Standard
IARC	International Agency for Research on Cancer



# Industrial Summit Technology

## SAFETY DATA SHEET

Date Updated: June 01, 2015

Product Name: Skybond® 701 Polyimide Resin

ICAO/IATA	International Civil Aviation Organization/International Air Transport Association
IMO/IMDG	International Maritime Organization/International Maritime Dangerous Goods Code
LC <sub>50</sub>	Lethal concentration to 50% of exposed laboratory animals
LD <sub>50</sub>	Lethal dose to 50% of exposed laboratory animals
MSHA	US Mine Safety and Health Administration
NIOSH	US National Institute of Occupational Safety and Health
NA	Not available
NTP	National Toxicology Program
OARS	Occupational Alliance for Risk Science
OSHA	US Occupational Safety Health Administration
RQ	Reportable quantity
SARA	Superfund Amendments and Reauthorization Act
SDS	Safety data sheet
TSCA	Toxic Substances Control Act
UN	United Nations
US/USA	United States
WEEL	Workplace Environmental Exposure Levels

Although the information set forth herein (herein after "Information") are presented in good faith and believed to be correct as of the date hereof, I.S.T. Corporation makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will I.S.T. Corporation be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS